2.6系列选型规则/Group 2.6 Ordering Code Rules

B	H	P	2.6	A1	D	10	C1	E0	省略/omit	省略/omit	省略/omit
博顿 Boden	材质 Material	功能 Function	系列 Group	前盖 Front cover	旋向 Rotation	排量 Displacement	轴伸 Shaft	泵体油口 Ports	特殊结构 Special structure	可选项 Options	其他 Other

- H — 前、后盖材料为铸铁压力 Front and end cover material cast iron
- P — 泵 Pump
- 2.6 — 2.6系列 Group 2.6
- 2.6Y — 2.6Y系列 Group2.6Y
- D — 顺时针转 Clockwise
- S — 逆时针转 Counter clockwise
- 排量 Displacement: 6, 8, 10, 12, 14, 16, 19, 22, 25, 28, 30, 32, 36, 38, 40
- 特殊设计 special designing

可选项 Options

	省略-温度范围在-10℃~+80℃,进油口最高绝对压力为3bar。 Omit-Range between -10℃ and +80℃,inlet pressure up to max. 3 bar absolute.
V	适用于高温介质，温度范围在-10℃~+120℃。 Version suitable for fluid at hi-temperatures, range between -10℃ and +120℃.
H	适用于低温介质，温度范围在-40℃~+80℃. Version suitable for fluid at low-temperatures, range between -40℃ and +80℃.
N	适用于进油口最大绝对压力3~10bar。 Version suitable for inlet pressure up to max. 3 and 10 bar absolute.

如需其它特殊选项请联系本公司工程师
For other special options, please contact our engineers.

前盖 Front cover

A1	菱形前盖(止口φ82.55) Diamond front cover (centering φ82.55mm)	
A2	菱形前盖(止口φ101.6) Diamond front cover (centering φ101.6mm)	
B0	方形前盖（止口φ50.8） Square front cover (centering φ50.8mm)	

轴伸 Shaft

C1	平键轴φ18 straight keyed φ18	
C2	平键轴φ19.05 straight keyed φ19.05	
C6	平键轴φ22.2 straight keyed φ22.2	
H1	矩形花键轴 Rectangle spline shaft ⌋⌊ 4-18x15x5	
H2	矩形花键轴 Rectangle spline shaft ⌋⌊ 6-20x16x4	
S0	渐开线花键轴 Involute spline shaft EXT12Z-1.5m-30°	
S1	SAE花键轴 SAE spline shaft DP16/32-30°-10T	
S2	SAE花键轴 SAE spline shaft DP16/32-30°-11T	
S3	SAE花键轴 SAE spline shaft DP16/32-30°-13T	

泵体油口 Ports

E_	矩形法兰 Rectangular flange	
F_	矩形法兰 Rectangular flange	
F_	矩形法兰 Split flange	
Z_	公制螺纹（M） Metric thread	
L_	英制管螺纹(G) Gas thread	
U_	美制管螺纹(UNF-2B) UNF thread	
R_	英制锥螺纹(PT) PT thread	
X	泵体无油口 Body without ports	

特殊结构 Special structure

	省略-默认普通 omit-regular	
—	后盖带进出油口 Back cover with inlet and outlet	